iM1822


P-Channel Enhancement Mode MOSFET

Datasheet

1. Product Information

1.1 Features

- Advanced Trench Cell Design
- RoHS Compliant and Halogen Free
- Reliable and Rugged



1.2 Package Type

PDFN5X6A-EP1-8L

1.3 Quick Reference

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Limiting Values						
P_{tot}	Total Power Dissipation	T_C = 25 ℃	-	-	43	W
I_D	Drain Current	T_C = 25 ℃, V_{GS} = -10 V	-	-	-33.7	A
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown	V_{GS} = 0 V, I_{DS} = -250 μA	-60	-	-	V
$R_{DS(ON)}$ Note2	On-State Resistance	V_{GS} = -10 V, I_{DS} = -20 A	-	17	21.5	mΩ
		V_{GS} = -4.5V, I_{DS} = -10 A	-	23	31	



Note 1：Surface Mounted on 1 in^2 pad area, t ≤ 10 sec.
Note 2：Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
Note 3：Limited by bonding wire.

2. Ordering Code & Marking Information

Ordering Code	Marking Information
iM1822	iM1822 XXXXXX X : Date Code

© 2025inergy Technology Inc. All rights reserved.

3. Pin Description

Pin	Description	Simplified Outline	Symbol
1~3	Source		
4	Gate		
5~6	Drain		

4. Limiting Values

Symbol	Parameter		Rating	Unit
V_{DS}	Drain-Source Voltage		-60	V
V_{GS}	Gate-Source Voltage		± 20	V
I_D	Drain Current	T_C = 25 ℃	-33.7	A
		T_C = 100 ℃	-21	A
I_{DM}	Pulsed Source Current	T_C = 25 ℃	-115	A
I_S	Diode Forward Current	T_C = 25 ℃	-33.7	A
E_{AS}	Single Pulsed Avalanche Energy	L= 1.0mH	-208	mJ
P_{tot}	Total Power Dissipation	T_C = 25 ℃	43	W
$R_{\theta JA}$ Note1	Thermal Resistance- Junction to Ambient		62	℃ / W
$R_{\theta JC}$	Thermal Resistance- Junction to Case		2.9	℃ / W
T_{stg}	Storage Temperature		-55~150	℃
T_J	Junction Temperature		150	℃

Note 1：Surface Mounted on 1 in^2 pad area, t ≤ 10 sec.
Note 2：Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
Note 3：Limited by bonding wire.

© 2025inergy Technology Inc. All rights reserved.

5. Electrical Characteristics (T_A = 25 °C Unless Otherwise Noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0 V, I_{DS} = -250 μA	-60	-	-	V
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_{DS} = -250 μA	-1	-	-3	V
I_{DSS}	Drain Leakage Current	V_{DS} = -48V, V_{GS} = 0 V	-	-	-1	μA
I_{GSS}	Gate Leakage Current	V_{DS} = 0 V, V_{GS} = ± 20 V	-	-	±100	nA
$R_{DS(ON)}$ Note1	On-State Resistance	V_{GS} = -10 V, I_{DS} = -20 A	-	17	21.5	mΩ
		V_{GS} = -4.5V, I_{DS} = -10A	-	23	31	
Diode Characteristics						
V_{SD} Note1	Diode Forward Voltage	I_{SD} = -20 A, V_{GS} = 0 V	-	-	-1.3	V
t_{rr}	Reverse Recovery Time	I_{DS}= -20 A, V_{GS} = 0 V	-	23	-	nS
Q_{rr}	Reverse Recovery Charge	dI_{SD}/dt = -100 A/μs	-	23	-	nC
Dynamic Characteristics Note2						
C_{iss}	Input Capacitance	V_{GS} = 0 V, V_{DS} = -30 V Frequency = 1 MHz	-	4607	-	pF
C_{oss}	Output Capacitance		-	180	-	
C_{rss}	Reverse Transfer Capacitance		-	117	-	
t_d(on)	Turn-on Delay Time	V_{DS} = -30 V, V_{GEN} = -10 V, R_G = 3.9 Ω, R_L =1.5Ω, I_{DS} = -20 A	-	10	-	nS
t_r	Turn-on Rise Time		-	33	-	
t_d(off)	Turn-off Delay Time		-	99	-	
t_f	Turn-off Fall Time		-	45	-	
Gate Charge Characteristics Note2						
Q_g	Total Gate Charge	V_{DS} = -30 V, V_{GS} = -10 V, I_{DS} = -20A	-	75	-	nC
Q_{gs}	Gate-Source Charge		-	21	-	
Q_{gd}	Gate-Drain Charge		-	10	-	

Note 1: Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
Note 2: Guaranteed by design, not subject to production testing.


© 2025inergy Technology Inc. All rights reserved.

6. Typical Characteristics


Power Capability




Current Capability



Safe Operating Area




Transient Thermal Impedance




© 2025inergy Technology Inc. All rights reserved.

6. Typical Characteristics


Output Characteristics




On Resistance



Transfer Characteristics




Normalized Threshold Voltage




© 2025inergy Technology Inc. All rights reserved.

6. Typical Characteristics


Normalized On Resistance




Diode Forward Current



Capacitance



Gate Charge



© 2025inergy Technology Inc. All rights reserved.

Important Notice

1. inergy Technology Inc. reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

2. The Products of inergy Technology Inc. have been tested, verified and passed by our specifications and standards, and are 100% inspected before delivery from the factory. It is strongly recommended that the customers shall perform verifications of the functionality, compatibility, and reliability of the environment or platform that you used. inergy Technology Inc. would not be liable for or guarantee anything that is related to the functionality, compatibility, and reliability of the environment or platform used by the customers.

© 2025inergy Technology Inc. All rights reserved.