iM4508


Dual N-Channel Enhancement Mode MOSFET

Datasheet

1. Product Information

1.1 Features

- Advanced Trench Cell Design
- RoHS Compliant and Halogen Free
- Reliable and Rugged



1.2 Package Type

SOP-8L

1.3 Quick Reference

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Limiting Values						
P_{tot}	Total Power Dissipation	T_A = 25 ℃	-	-	1.9	W
I_D	Drain Current	T_A = 25 ℃, V_{GS} = 10 V	-	-	3	A
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown	V_{GS} = 0 V, I_{DS} = 250 μA	100	-	-	V
$R_{DS(ON)}$	On-State Resistance	V_{GS} = 10 V, I_{DS} = 2 A	-	87	108	mΩ
		V_{GS} = 4.5 V, I_{DS} = 1 A	-	117	152	



Note 1：Surface Mounted on 1 in^2 pad area, t ≤ 10 sec.
Note 2：Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
Note 3：Limited by bonding wire.

© 2024 inergy Technology Inc. All rights reserved.

2. Ordering Code & Marking Information

Ordering Code	Marking Information
iM4508	iM4508 XXXXX X : Date Code

3. Pin Description

Pin	Description	Simplified Outline	Symbol
1	Source (S1)	 Top View	
2	Gate (G1)		
3	Source (S2)		
4	Gate (G2)		
5,6	Drain (D2)		
7,8	Drain (D1)		

4. Limiting Values

Symbol	Parameter		Rating	Unit
V_{DS}	Drain-Source Voltage		100	V
V_{GS}	Gate-Source Voltage		± 20	V
I_D	Drain Current	T_A = 25 ℃	3	A
		T_A = 100 ℃	1.9	A
I_{DM} Note2	Pulsed Source Current	T_A = 25 ℃	12	A
I_S	Diode Forward Current	T_A = 25 ℃	3	A
P_{tot}	Total Power Dissipation	T_A = 25 ℃	1.9	W
$R_{\theta JA}$ Note1	Thermal Resistance- Junction to Ambient		65	℃ / W
T_{stg}	Storage Temperature		-55~150	℃
T_J	Junction Temperature		150	℃

Note 1：Surface Mounted on 1 in^2 pad area, t ≤ 10 sec.
Note 2：Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
Note 3：Limited by bonding wire.

© 2024 inergy Technology Inc. All rights reserved.

5. Electrical Characteristics (T_A = 25 °C Unless Otherwise Noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0 V, I_{DS} = 250 μA	100	-	-	V
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_{DS} = 250 μA	1	-	2	V
I_{DSS}	Drain Leakage Current	V_{DS} = 80 V, V_{GS} = 0 V	-	-	-1	μA
I_{GSS}	Gate Leakage Current	V_{GS} = ± 20 V, V_{DS} = 0 V	-	-	±100	nA
$R_{DS(ON)}$ Note1	On-State Resistance	V_{GS} = 10 V, I_{DS} = 2 A	-	87	108	mΩ
		V_{GS} = 4.5 V, I_{DS} = 1 A	-	117	152	
Diode Characteristics						
V_{SD} Note1	Diode Forward Voltage	I_{SD} =2 A, V_{GS} = 0 V	-	-	1.3	V
t_{rr}	Reverse Recovery Time	I_{DS} = 2 A, V_{GS} = 0 V dI_{SD}/dt = 100 A/μs	-	21	-	nS
Q_{rr}	Reverse Recovery Charge		-	14	-	nC
Dynamic Characteristics Note2						
C_{iss}	Input Capacitance	V_{GS} = 0 V, V_{DS} = 50 V Frequency = 1 MHz	-	157	-	pF
C_{oss}	Output Capacitance		-	28	-	
C_{rss}	Reverse Transfer Capacitance		-	4	-	
t_d(on)	Turn-on Delay Time	V_{DS} = 50 V, V_{GEN} = 10 V, R_G = 3.9 Ω, R_L = 25 Ω, I_{DS} = 2 A	-	2.8	-	nS
t_r	Turn-on Rise Time		-	1.7	-	
t_d(off)	Turn-off Delay Time		-	7.5	-	
t_f	Turn-off Fall Time		-	2.7	-	
Gate Charge Characteristics Note2						
Q_g	Total Gate Charge	V_{DS} = 50 V, V_{GS} = 10 V, I_{DS} = 2 A	-	5	-	nC
Q_{gs}	Gate-Source Charge		-	1	-	
Q_{gd}	Gate-Drain Charge		-	1.1	-	

Note 1: Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
Note 2: Guaranteed by design, not subject to production testing.


© 2024 inergy Technology Inc. All rights reserved.

6. Typical Characteristics


Power Capability




Current Capability



Safe Operating Area




Transient Thermal Impedance




© 2024 inergy Technology Inc. All rights reserved.


Output Characteristics




On Resistance



Transfer Characteristics




Normalized Threshold Voltage




© 2024 inergy Technology Inc. All rights reserved.


Normalized On Resistance




Diode Forward Current



Capacitance



Gate Charge



© 2024 inergy Technology Inc. All rights reserved.

Important Notice

1. inergy Technology Inc. reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

2. The Products of inergy Technology Inc. have been tested, verified and passed by our specifications and standards, and are 100% inspected before delivery from the factory. It is strongly recommended that the customers shall perform verifications of the functionality, compatibility, and reliability of the environment or platform that you used. inergy Technology Inc. would not be liable for or guarantee anything that is related to the functionality, compatibility, and reliability of the environment or platform used by the customers.

© 2024 inergy Technology Inc. All rights reserved.