
iM9435



P-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☑ Surface-mounted package
- ☑ Advanced trench cell design

1.2 Applications


- ☑ Portable appliances
- ☑ High speed switch
- ☑ Low power DC to DC Converter

1.3 Quick reference

- ☑ BV ≦ -30 V
- ☑ P_{tot} ≦ 2.5 W
- ☑ I_D ≦ -5.7 A
- ☑ $R_{DS(ON)}$ ≦ 50 mΩ @ V_{GS} = -10 V
  $R_{DS(ON)}$ ≦ 80 mΩ @ V_{GS} = -4.5 V


2. Pin Description


Pin	Description	Simplified Outline	Symbol
1,2,3	Source(S)		
4	Gate(G)		
5,6,7,8	Drain(D)		



Top View

SOP8





3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	T_A = 25 ℃		-30	V
V_{GS}	Gate-Source Voltage	T_A = 25 ℃		±25	V
I_D*	Drain Current	T_A = 25 ℃, V_{GS} = -10 V		-5.7	A
		T_A = 100 ℃, V_{GS} = -10 V		-3.6	A
I_{DM}*,**	Pulsed Drain Current	T_A = 25 ℃, V_{GS} = -10 V		-15	A
P_{tot}	Total Power Dissipation	T_A = 25 ℃		2.5	W
T_{stg}	Storage Temperature		-55	150	℃
T_J	Junction Temperature		-55	150	℃
I_S	Diode Forward Current	T_A = 25 ℃		-2	A
$R_{\theta JA}$*	Thermal Resistance- Junction to Ambient			50	℃/W

Notes :

* Surface Mounted on 1 in^2 pad area, t ≤ 10 sec

** Pulse width ≤ 300 μs, duty cycle ≤ 2 %


4. Marking Information

Product Name	Marking
iM9435	iM9435 XXXXX X : Date Code

5. Ordering Code

iM9435 □ └── Assembly Material	Assembly Material G: Halogen and Lead Free Device

Note: inergy defines “Green” as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)



6. Electrical Characteristics (T_A = 25 °C Unless Otherwise Noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0 V, I_{DS} = - 250 µA	- 30	-	-	V
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_{DS} = - 250 µA	- 1	- 1.5	- 2	V
I_{DSS}	Drain Leakage Current	V_{DS} = - 24 V, V_{GS} = 0 V	-	-	- 1	µA
		T_J = 85 °C	-	-	- 30	µA
I_{GSS}	Gate Leakage Current	V_{GS} = ± 25 V, V_{DS} = 0 V	-	-	± 100	nA
$R_{DS(ON)}$[a]	On-State Resistance	V_{GS} = - 10 V, I_{DS} = - 5.7 A	-	40	50	mΩ
		V_{GS} = - 4.5 V, I_{DS} = - 2 A	-	60	80	
Diode Characteristics						
V_{SD}[a]	Diode Forward Voltage	I_{SD} = - 5 A, V_{GS} = 0 V	-	- 0.8	- 1.1	V
t_{rr}	Reverse Recovery Time	I_{SD} = - 5 A, dI_{SD}/dt = 100 A/µs	-	8.9	-	ns
Q_{rr}	Reverse Recovery Charge		-	4.5	-	nC
Dynamic Characteristics[b]						
R_G	Gate Resistance	V_{GS} = V_{DS} = 0 V, F = 1 MHz	-	11	-	Ω
C_{iss}	Input Capacitance	V_{GS} = 0 V, V_{DS} = -15 V Frequency = 1 MHz	-	630	-	pF
C_{oss}	Output Capacitance		-	72	-	
C_{rss}	Reverse Transfer Capacitance		-	61	-	
t_d(on)	Turn-on Delay Time	V_{DS} = - 15 V, V_{GEN} = - 10 V, R_G = 3.9 Ω, R_L = 3 Ω, I_{DS} = - 5 A	-	9.7	-	nS
t_r	Turn-on Rise Time		-	23	-	
t_d(off)	Turn-off Delay Time		-	72	-	
t_f	Turn-off Fall Time		-	39	-	
Gate Charge Characteristics[b]						
Q_g	Total Gate Charge	V_{GS} = - 10 V, V_{DS} = - 15 V, I_{DS} = - 5 A	-	12		nC
Q_{gs}	Gate-Source Charge		-	3.2	-	
Q_{gd}	Gate-Drain Charge		-	1.6	-	


Notes :


a : Pulse test ; pulse width ≤ 300 µs, duty cycle ≤ 2%


b : Guaranteed by design, not subject to production testing

7. Typical Characteristics











7. Typical Characteristics (cont.)


Output Characteristics




On Resistance



Transfer Characteristics




Normalized Threshold Voltage




7. Typical Characteristics (cont.)


Normalized On Resistance




Diode Forward Current




Capacitance




Gate Charge







8. Package Dimensions

SOP- 8







Symbol	Dimensions In Millimeters	
	MIN.	MAX.
A	1.35	1.75
A1	0.00	0.25
A2	1.15	1.50
D	4.80	5.00
E	5.80	6.20
E1	3.80	4.00
c	0.19	0.27
b	0.33	0.53
e	1.27 BSC	
L	0.40	1.27

Notes：

1. Jedec outline ： MS-012AA
2. Dimensions ” D ” does not include mold flash, protrusions and gate burrs shall not exceed .15 mm (.006 in) per side .
3. Dimensions “ E1 ” does not include inter-lead flash, or protrusions. Inter-lead flash and protrusions shall not exceed .25 mm (.010 in) per side.