iMN03N10DM



N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☑ Surface-mounted package
- ☑ Advanced trench cell design

1.2 Applications


- ☑ LCD TV appliances
- ☑ LCDM appliances
- ☑ High power inverter system

1.3 Quick reference

- ☑ BV ≧ 100 V
- ☑ P_{tot} ≦ 333 W
- ☑ I_D ≦ 90 A
- ☑ $R_{DS(ON)}$ ≦ 3.7mΩ @ V_{GS} = 10 V
- ☑ $R_{DS(ON)}$ ≦ 5.7mΩ @ V_{GS} = 4.5 V


2. Pin Description

Pin	Description	Simplified Outline	Symbol
1	Gate(G)		
2	Drain(D)		
3	Source(S)		



Top View

TO263-3L





3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	T_C = 25 ℃	-	100	V
V_{GS}	Gate-Source Voltage	T_C = 25 ℃	-	± 20	V
I_D*,***	Drain Current (DC)	T_C = 25 ℃, V_{GS} = 10 V	-	90	A
		T_C = 100 ℃, V_{GS} = 10 V	-	90	A
I_{DM}*,**,***	Drain Current (Pulsed)	T_C = 25 ℃, V_{GS} = 10 V	-	360	A
P_{tot}	Drain power dissipation	T_C = 25 ℃	-	333	W
T_{stg}	Storage Temperature		- 55	175	℃
T_J	Junction Temperature		-	175	℃
I_S	Continuous-Source Current	T_C = 25 ℃	-	90	A
E_{AS}*	Single Pulsed Avalanche Energy	V_{DD} = 50V , L= 0.1mH	-	150	mJ
$R_{\theta JA}$*	Thermal Resistance- Junction to Ambient		-	36.2	℃/W
$R_{\theta JC}$*	Thermal Resistance- Junction to Case		-	0.45	

Notes :

* Surface Mounted on 1 in^2 pad area, t ≤ 10 sec

** Pulse width ≤ 300 μs, duty cycle ≤ 2 %

*** Limited by bonding wire



4. Marking Information

Product Name	Marking		
iMN03N10DM		03N10M XXXXXX	X : Date Code

5. Ordering Code

iMN03N10DM	Assembly Material: Halogen and Lead Free Device

Note: inergy defines " Green " as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)



6. Electrical Characteristics (T_A=25 ° Unless Otherwise Noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS} = 0 V, I_{DS} = 250 µA	100	-	-	V
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_{DS} = 250 µA	1	-	3	V
I_{DSS}	Drain Leakage Current	V_{DS} = 80 V, V_{GS} = 0 V	-	-	1	µA
I_{GSS}	Gate Leakage Current	V_{GS} = ± 20 V, V_{DS} = 0 V	-	-	±100	nA
$R_{DS(ON)}$[a]	On-State Resistance	V_{GS} = 10 V, I_{DS} = 20 A	-	3.1	3.7	mΩ
		V_{GS} = 4.5 V, I_{DS} =10 A	-	4.4	5.7	
Diode Characteristics						
V_{SD}[a]	Diode Forward Voltage	I_{SD} = 20 A, V_{GS} = 0 V	-	-	1.3	V
t_{rr}	Reverse Recovery Time	I_{DS} = 20 A, V_{GS} = 0 V dI_{SD}/dt = 100 A/µs	-	82	-	nS
Q_{rr}	Reverse Recovery Charge		-	154	-	nC
Dynamic Characteristics[b]						
C_{iss}	Input Capacitance	V_{GS} = 0 V, V_{DS} = 50 V Frequency = 1 MHz	-	4748	-	pF
C_{oss}	Output Capacitance		-	788	-	
C_{rss}	Reverse Transfer Capacitance		-	46	-	
t_d(on)	Turn-on Delay Time	V_{DS} = 50 V, V_{GEN} = 10 V, R_G = 4.5 Ω, R_L = 2.5 Ω, I_{DS} = 20 A	-	14	-	nS
t_r	Turn-on Rise Time		-	47	-	
t_d(off)	Turn-off Delay Time		-	81	-	
t_f	Turn-off Fall Time		-	102	-	
Gate Charge Characteristics[b]						
Q_g	Total Gate Charge	V_{DS} = 50 V, V_{GS} = 10 V, I_{DS} = 20 A	-	96	-	nC
Q_{gs}	Gate-Source Charge		-	17	-	
Q_{gd}	Gate-Drain Charge		-	23	-	


Notes :


a : Pulse test ; pulse width ≤ 300 µs, duty cycle ≤ 2%


b : Guaranteed by design, not subject to production testing




7. Typical Characteristics















7. Typical Characteristics (cont.)















7. Typical Characteristics (cont.)












8. Package Dimensions

TO263-3L



Symbol	Dimensions In Millimeters	
	MIN.	MAX.
A	4.40	4.80
b	0.76	1.00
L4	0.00	0.25
C	0.36	0.50
L3	1.50 REF	
L1	2.29	2.79
E	9.80	10.40
E1	7.40 REF	
c2	1.25	1.45
b2	1.17	1.47
D	8.60	9.00
D1	5.10 REF	
e	2.54 REF	
L	14.6	15.8
θ	0° ± 3°	
L2	1.27 REF	